CLAIMS

What is claimed is:

1. – 35. (Canceled)

- 36. (Currently Amended) An Integrated integrated biosensor and simulation system comprising: aat least one sensor biosensor for sensing a biological target to generate a signal; and a simulator for using the signal and a model of the target to generate a therapeutic or diagnostic output; and wherein said sensor is reconfigurable by said simulator.
- 37. (**Previously presented**) The system of claim 36 wherein: the sensor senses a food material for consumption by the biological target to generate a second signal, the simulator further using the second signal to generate the therapeutic or diagnostic output.
- 38. (**Previously presented**) The system of claim 36 wherein: the simulator generates the output according to a regulatory condition.
- 39. (Previously presented) The system of claim 36 wherein: the sensor couples to the simulator via a programmable switch.
- 40. (Currently Amended) Automated sensor and simulation A method comprising the steps of: sensing with a biosensor a biological target to generate a signal; simulating with a simulator using the signal and a model of the target to generate a therapeutic or diagnostic output; and wherein said simulator reconfigures said sensor biosensor.
- 41. (Previously presented) The method of claim 40 wherein: the sensor senses a food material for consumption by the biological target to generate a second signal, the simulator further using the second signal to generate the therapeutic or diagnostic output.
- 42. **(Previously presented)** The method of claim 40 wherein: the simulator generates the output according to a regulatory condition.

- 43. (Previously presented) The method of claim 40 wherein: the sensor couples to the simulator via a programmable switch.
- 44. (New) The method of claim 40, wherein said sensor is implanted in a subject's mouth, larynx, blood vessel, vein, nose, ear, eye, heart, brain, lymph node, lung, breast, stomach, pancreas, kidney, colon, rectum, ovary, uterus, bladder or prostate.
- 45. (New) The method of claim 40, wherein said biosensor comprises an array of at least two sensors.
- 46. (New) The method of claim 45, wherein said at least two sensors are capable of sensing two different biological targets.
- 47. (New) The method of claim 46, wherein said different biological targets are selected from a group consisting of DNA, RNA, peptide, antibody, antigen, tissue factor, virus, lipid, fatty acid, steroid, neurotransmitter, carbohydrate, free radical, neural, chemical, metabolite and cell.
- 48. (New) The method of claim 40, wherein said reconfiguring comprises activating or deactivating said biosensor.
- 49. (New) The method of claim 45, wherein said reconfiguring comprises activating or deactivating at least one of said at least two sensors.
- 50. (New) The method of claim 40, wherein said reconfiguring comprise hardware reconfiguration.
- 51. (New) The system of claim 36, wherein said simulator is capable of activating or deactivating said sensor.
- 52. (New) The system of claim 36, wherein said sensor is capable of functioning in a subject's mouth, larynx, blood vessel, vein, nose, ear, eye, heart, brain, lymph node, lung, breast, stomach, pancreas, kidney, colon, rectum, ovary, uterus, bladder or prostate.

- 53. (New) The system of claim 36, wherein said biosensor comprises said at least one sensor and at least a second sensor.
- 54. (New) The system of claim 53, wherein said at least one sensor and said at least second sensor are capable of sensing two different biological targets.
- 55. (New) The system of claim 54, wherein said different biological targets are selected from a group consisting of DNA, RNA, peptide, antibody, antigen, tissue factor, virus, lipid, fatty acid, steroid, neurotransmitter, carbohydrate, free radical, neural, chemical, metabolite and cell.